



Part Number: 83005

Hook-Up/Lead Wire UL AWM Style 1213, (1) 22 AWG (7x30) SPC, TFE, 105°C

Request Sample

Product Description

One 22 AWG stranded (7x30) silver plated copper conductor, TFE insulation.

Technical Specifications

Physical Characteristics (Overall)

Conductor

Oonaa	Cloi			
AWG	Stranding	Material	N	o. of Conductors
22	7x30	SCC - Silver-coated Cop	per 1	
Condu	ictor Count:		1	
Condu	ıctor Size:		22 AW	G

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
TFE - Tetrafluoroethylene	0.049 in	0.01 in

Outer Jacket Material

Material	Nominal Diameter
No Jacket	0.05 in

Electrical Characteristics

Conductor DCR



Shielding: Unshielded

Current

Element	Max. Recommended Current [A]
Mil-Std-975M Table 3.16 (single wire)	Mil-Std-975M Table 3.16 (single wire): 4.5 amps

Voltage

Description	Voltage Rating [V]	
Mil-W-16878/4	600 V RMS Mil-W-16878/4	

Temperature Range

UL Temp Rating:	105°C
Operating Temp Range:	-70°C To +200°C

Mechanical Characteristics

Bulk Cable Weight:	4 lbs/1000ft

Standards

UL AWM Style:	1213
Military Specification:	NEMA HP3, MIL-W-16878/4

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	600 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No

Part Number

Variants

Item #	Color	Footnote
83005 010100	Black	E
83005 0101000	Black	
83005 006100	Blue, Light	E
83005 0061000	Blue, Light	ES
83005 001100	Brown	E
83005 0011000	Brown	ES
83005 008100	Gray	E
83005 0081000	Gray	ES
83005 005100	Green, Dark	E
83005 0051000	Green, Dark	ES
83005 003100	Orange	E
83005 0031000	Orange	ES
83005 002100	Red	E
83005 0021000	Red	ES
83005 007100	Violet	E
83005 0071000	Violet	ES
83005 009100	White	E
83005 0091000	White	ES
83005 004100	Yellow	E
83005 0041000	Yellow	ES

Footnote:	E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'.	
Footnote:	S - STRIPING ADDERS FOR TYPES E AND EE: 1, 2, 3 STRIPES. MINIMUM ORDER 10,000' PER STRIPE COMBINATION. (SEE STRIPING ADDER TABLE)	

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.